



# Smart App Office Rackmount Series

OR6000E/1000E/1500ELCDRM1U

**CyberPower**<sup>®</sup>  
Reliability. Quality. Value.

## Technical Specification

| Model                                     | OR600ELCDRM1U  | OR1000ELCDRM1U | OR1500ELCDRM1U |
|---|--|----------------|----------------|
| <b>Configuration</b>                      |  |                |                |
| Capacity (VA / Watts)                     | 600 / 360  | 1000 / 600     | 1500 / 900     |
| Energy-Saving Technology                  | Yes  |                |                |
| <b>Input</b>                              |  |                |                |
| Frequency Range                           | 47 Hz - 63 Hz (Auto Sensing)   |                |                |
| Input Plug Type                           | IEC 320 C14  |                |                |
| <b>Output</b>                             |  |                |                |
| UPS Outlets (Numbers)                     | (6) IEC (Backup x 4)   |                |                |
| On Battery Output Voltage                 | Simulated Sinewave at 230 Vac +/- 10%  |                |                |
| On Battery Output Frequency               | 50 Hz / 60 Hz +/- 1%   |                |                |
| Transfer Time (Typical)                   | 4ms  |                |                |
| Overload Protection                       | On Utility: Circuit Breaker & Internal Current Limiting<br>On Battery: Internal Current Limiting |                |                |
| AVR                                       | Single Boost   |                |                |
| <b>Surge Protection and Filtering</b>     |  |                |                |
| Lightning / Surge Protection              | Yes  |                |                |
| DSL / Phone / FAX / Modem Protection      | RJ11 / RJ45 (One In / One Out)   |                |                |
| <b>Physical</b>                           |  |                |                |
| Dimensions (H x W x D) (mm)               | 44 x 430 x 235   | 44 x 433 x 389 | 44 x 433 x 495 |
| Weight (kg)                               | 8.1  | 16.1           | 19.4           |
| <b>Battery</b>                            |  |                |                |
| Sealed Maintenance Free Lead Acid Battery | 6V / 9AH x 2   | 6V / 7AH x 4   | 6V / 9AH x 4   |
| User Replaceable                          | Yes  |                |                |
| Typical Recharge Time                     | 8 Hours  |                |                |
| <b>Runtimes</b>                           |  |                |                |
| Half-load / Full-load (mins)              | 12 / 4   | 14 / 4         | 11 / 3         |
| <b>Status Indicators</b>                  |  |                |                |
| Indicators                                | Power On, Wiring Fault   |                |                |
| Audible Alarms                            | On Battery, Low Battery, Overload  |                |                |
| Multi-function LCD Readout                | Yes  |                |                |
| <b>Communication</b>                      |  |                |                |
| PowerPanel <sup>®</sup> Business Edition  | Windows 7 / Vista / XP / 2000, Server 2008 / 2003  |                |                |
| <b>Management</b>                         |  |                |                |
| Self Test                                 | Yes  |                |                |
| Auto-Charge / Auto-Restart                | Yes  |                |                |
| Connectivity Ports                        | USB, Serial  |                |                |
| SNMP/HTTP Capable                         | Optional   |                |                |

#All specifications are subject to change without notice. ©2011 Cyber Power Systems. All Trademarks are the property of their owners.

## Packaging Content:



Product Unit



USB Cable



Phone Cable



User Manual



Software CD

**DISTRIBUTED BY:**

CyberPower's  
Manufacturing  
Facilities are  
ISO 9001:2000,  
ISO 14000, and  
QC080000  
Approved

